

CES-EQ17-D340

嵌入式无风扇边缘计算系列

Intel® Skylake-S/Kabylake-S系列LGA1151奔腾/赛扬/酷睿处理器
Q170芯片组, 3网口, 最大支持6串口
9个USB, 16bit DIO, 可选9-36V宽压输入

采用Intel® Skylake-S/Kabylake-S系列LGA1151奔腾/赛扬/酷睿处理器, 搭载Q170芯片组, 拥有丰富I/O接口, 同时具有高度灵活的扩展性, 可以支持2xSATA3.0 RAID 0/1, 可扩展PCIEX16, PCIEX8, PCIEX4, PCIEX1及PCI插槽, 标准19-24V DC电压输入, 可选9-36V宽压, 结构采用无风扇设计, 稳定性高, 可广泛应用于工业自动化、机器视觉、能源环保、设备检测、金属探测等领域。



采用Skylake-S/Kabylake-S系列LGA1151奔腾/赛扬/酷睿处理器, 搭载Q170芯片组
支持双通道DDR4 2133MHz SODIMM内存插槽, 内存容量最大可达32GB
支持三个千兆网口

支持VGA, HDMI及DP++ 三显
内置2 x 2.5寸HDD/SSD支架

内置1 x Mini-PCIe/mSATA槽, 1 x M.2 2230 wifi卡槽及1 x M.2 2242扩展槽, 支持多种模块扩展

内置1 x M.2 3042/3052可选卡槽, 可扩展5G模块

内置1 x 内置USB2.0接口, 可接加密狗

可支持PCIe X 16, PCIe X 8, PCIe X 4, PCIe X 1及PCI扩展插槽

标准19-24V DC电源输入, 可选宽压9-36V DC-IN






规格 Specification

系统 System		外部接口 External I/O	
处理器 Processor	Intel® 6th/7th Gen. Pentium®, Celeron®, Core™ i3/i5/i7	网口 Ethernet	2 x RJ45, Intel® i211AT GbE (10/100/1000 Mbps) 1 x RJ45, Intel® I219LM GbE (10/100/1000 Mbps)
芯片组 Chipset	Intel Q170 PCH	显示 Video	1 x VGA: max resolution up to 1920 x 1200 1 x HDMI: max resolution up to 4096 x 2160 1 x DP++: max resolution up to 4096 x 2304
内存 Memory	2 x DDR4 2133MHz SO-DIMM, Up to 32GB	音频 Audio	1 x Line-out, 1 x Mic-in, Realtek® ALC269 HD Audio codec
图形 Graphics	Intel® HD Graphics 530/510 (Intel 6th Gen. CPU) Intel® HD Graphics 630 (Intel 7th Gen. CPU)	串口 COM	4 x RS232/422/485 auto-flow 2 x RS232 (optional by internal pin head)
存储 Storage	2 x 2.5" SATA 3.0 HDD/SSD Bay, support RAID0/1 1 x mSATA slot 1 x M.2 2242 SSD slot	USB	8 x USB 3.0, 1 x internal USB2.0
操作系统 OS	Windows 7/8/10, Linux	GPIO	1 x 16bit programmable GPIO (default 3.3V, 5V optional)
看门狗定时器 Watchdog Timer	Programmable 255 levels timer interval, from 1~255 sec/min	按钮 Button	1 x Power button
机构 Mechanical		指示灯 Indicators	1 x Power LED (Green for Power-on, Blink for Sleep mode, Off for Power-off)
外观 Housing	铝合金 Aluminum Alloy		1 x HDD LED (Red blink for Data read or write)
安装方式 Mounting	桌面式 (Desk-Mount), 壁挂式 (Wall-Mount)		2 x COM1 LED for Rx1 and Tx1
尺寸 Dimension	200 x 230 x 78 mm		2 x COM2 LED for Rx2 and Tx2
重量 Weight	3.5kg		1 x Wifi communication LED (yellow blink for communication)
机械冲击 Shock	Operation: 10G@11ms	1 x 4G communication LED (yellow blink for communication)	1 x PL1 for user definition (can indicate CPU temperature, voltage detect, CPU/SYS Fan speed, etc)
环境 Environmental		远程开关 Remote ON-OFF	1 x Remote ON-OFF
操作温度 OperatingTemp.	-10°C ~ 40°C with 0.7m/s air flow (with 65W CPU and industrial SSD) -10°C ~ 50°C with 0.7m/s air flow (with 35W CPU and industrial SSD) 0°C ~ 30°C with 0.7 m/s air flow (HDD)	内部接口 Internal I/O	
存储温度 Storage Temp.	-40°C ~ 85°C	扩展接口 Expansion	1 x Mini-PCIe slot (co-lay with mSATA) 1 x M.2 2242 Key-M PCIe slot (co-lay with M.2 2242 SSD slot) 1 x M.2 2230 Key-E slot for Wifi module 1 x M.2 3042/3052 Key-B for 5G communication module (optional)
湿度 Relative Humidity	5% ~ 95%, 非凝结状态 Non-condensing	SIM 卡	1 x SIM Card socket for 3G/4G module 1 x SIM Card socket for 5G module
振动 Vibration	SSD: 5~500Hz, 2Grms operation HDD: 5~500Hz, 1Grms operation	认证 Certification	
机械冲击 Shock	Operation: 10G@11ms Non-operation: 30G@11ms	安规认证 Safety Certification	CCC, CE, FCC
电源 Power			
电源输入 Power Input	19-24V DC, 4-pin phoenix connector (9-36V DC optional with power board)		

订购清单 Order List

	型号 Model Name	描述 Description		型号 Model Name	描述 Description
标配 Standard	CEA-GP00-CON0	1 x 16bit GPIO conn (3.50), female	选配 Optional	CEA-150L-IS00	150cm AC power cord
	CEA-PWDC-CAB4	1 x 4P DC in Phoenix conn (5.00), female		CEA-EQ17-PWBD	9-36V DC power board for CES-EQ17/EH11
	CEA-RESW-CAB0	1 x 2P Remote Phoenix conn (3.50), female		CEA-EQ17-2S20	2 slots module (1 x PCIeX16 slot and 1 x PCIeX4 slot)
	CEA-SKIT-EQ17	standard wall mount kit		CEA-EQ17-2S11	2 slots module (1 x PCIeX16 slot and 1 x PCI slot) for
				CEA-EQ17-4S13	4 slots module (1 x PCIeX16 slot and 3 x PCI slot) for
				CEA-EQ17-4S40	4 slots module (1 x PCIeX8 slot and 3 x PCIeX4) slot
				CEA-150W-LT00	LITEON 150W adapter, 19.5V @7.7A, 4pin terminal
				CEA-180W-LT00	LITEON 180W adapter, 19.5V @9.23A, 4pin terminal
				CEA-230W-LT00	LITEON 230W adapter, 19.5V @11.8A, 4pin terminal
				CEA-330W-LT00	LITEON 330W adapter, 19.5V @16.6A, 4pin terminal
				CEA-CM15-CAB0	1xCOM cable, 2x5P, 150mm, black

■ 尺寸 Dimension (Unit:mm)



注

产品配置请以合同或实物为准,如有修改恕不另行通知;
 版权为桦汉科技所有,未经桦汉科技书面许可,样本中的任何内容不得被复制或抄袭用于任何目的。

©中国印刷
 Number:MKT1005A0A-2-15(20.08.25)